

Hull and Patio Wax by Lustersheen

Lustersheen *Hull and Patio Wax*, unlike our wood and antique care waxes, is a high solids wax specially formulated to be used on the exterior.

Hull and Patio Wax is ideal as the seasonal pick me up to many patio furniture pieces. Lustersheen's *Hull and Patio Wax* works well to provide a lustrous shine to weathered and bleached out patio table tops. As a high performance exterior sealing wax, Hull and

Patio Wax is excellent for the preventive maintenance on many patio furniture pieces and can be used easily on a regular as needed basis.

Hull and Patio Wax is exceptional for patio table tops and the perfect polish to shine the table tops used on the porch for outdoor events, backyard picnics, barbecues and family outings.

Hull and Patio Wax is a high volume solids wax specifically engineered to seal and protect all above water surfaces from UV and salt water degradation. This product will restore shine to a vessels topsides and all areas above the waterline.

As a *Hull Wax* and polish designed for a boats topside, it helps seal the microscopic

pores in the boats gel-coat caused by UV damage. These same properties make this the ideal polish for porch and deck woodwork and furniture, and particularly suitable for the enhancing and protecting of patio table tops.

Hull and Patio Wax makes the boat's various above water substrates (and thus your patio table tops) much easier to clean and resistant to staining.

Hull Wax should never be used below the waterline as it will stop the adhesion of any paint system and if applied over anti fouling will effectively block the chemical interface between the paint and the seawater.



www.Lustersheen.com



Application method:

- Apply with a soft lint-free cloth.
- Buff within 5 minutes of application.
- For a higher shine and ease of buffing use the Burnisher aka Pine Brush.
- Clean tools using Mineral Spirits.

Specifications:

Areas of use: Patio and deck woodwork and furniture.; Patio slate and quarry table tops; Various exterior slate, and quarry tile and stonework not used for flooring; Boat Hulls and topsides above the waterline; Over GRP gel-coat, Paint, Varnish, and Stainless Steel. (Not for floor use as it is very slippery when wet.)

Physical Constants:

Color: Clear

Finish: High Shine (not intended for floors)

Volume solids: 26 - 28%

Theoretical spreading rate: 30 - 50 sq. ft. per lb

Flash point: 42°C Specific gravity: 0.78

Dry to touch: Buff within 5 minutes of application

Over-coating time: NA

Packaging: 450 ml tin / 15 oz

MSRP: \$ 20.95

www.Lustersheen.com

866-343-3377 or 800-274-9299

Fax: 212-504-9550